

Scala Syntax Summary

Language Elements Seen So Far:

We have seen language elements to express types, expressions and definitions.

Below, we give their context-free syntax in Extended Backus-Naur form (EBNF), where

| denotes an alternative,

[...] an option (0 or 1),

{...} a repetition (0 or more).

Types

```
Type          = SimpleType | FunctionType
FunctionType  = SimpleType '=>' Type
              | '(' [Types] ')' '=>' Type
SimpleType    = Ident
Types         = Type {',' Type}
```

A *type* can be:

- ▶ A *numeric type*: Int, Double (and Byte, Short, Char, Long, Float),
- ▶ The Boolean type with the values true and false,
- ▶ The String type,
- ▶ A *function type*, like Int => Int, (Int, Int) => Int.

Later we will see more forms of types.

Expressions

```
Expr          = InfixExpr | FunctionExpr
              | if '(' Expr ')' Expr else Expr
InfixExpr     = PrefixExpr | InfixExpr Operator InfixExpr
Operator      = ident
PrefixExpr    = ['+' | '-' | '!' | '~'] SimpleExpr
SimpleExpr    = ident | literal | SimpleExpr '.' ident
              | Block
FunctionExpr  = Bindings '=>' Expr
Bindings      = ident [':' SimpleType]
              | '(' [Binding {',' Binding}] ')'
Binding       = ident [':' Type]
Block         = '{' {Def ';' } Expr '}'
```

Expressions (2)

An *expression* can be:

- ▶ An *identifier* such as `x`, `isGoodEnough`,
- ▶ A *literal*, like `0`, `1.0`, `"abc"`,
- ▶ A *function application*, like `sqrt(x)`,
- ▶ An *operator application*, like `-x`, `y + x`,
- ▶ A *selection*, like `math.abs`,
- ▶ A *conditional expression*, like `if (x < 0) -x else x`,
- ▶ A *block*, like `{ val x = math.abs(y) ; x * 2 }`
- ▶ An *anonymous function*, like `x => x + 1`.

Definitions

```
Def           = FunDef | ValDef
FunDef       = def ident { '(' [Parameters] ')' }
              [ ':' Type ] '=' Expr
ValDef       = val ident [ ':' Type ] '=' Expr
Parameter    = ident ':' [ '='> ] Type
Parameters   = Parameter { ',' Parameter }
```

A *definition* can be:

- ▶ A *function definition*, like `def square(x: Int) = x * x`
- ▶ A *value definition*, like `val y = square(2)`

A *parameter* can be:

- ▶ A *call-by-value parameter*, like `(x: Int)`,
- ▶ A *call-by-name parameter*, like `(y: => Double)`.