

## Subtyping and Generics

# Polymorphism

Two principal forms of polymorphism:

- ▶ subtyping
- ▶ generics

In this session we will look at their interactions.

Two main areas:

- ▶ bounds
- ▶ variance

## Type Bounds

Consider the method `assertAllPos` which

- ▶ takes an `IntSet`
- ▶ returns the `IntSet` itself if all its elements are positive
- ▶ throws an exception otherwise

What would be the best type you can give to `assertAllPos`? Maybe:

# Type Bounds

Consider the method `assertAllPos` which

- ▶ takes an `IntSet`
- ▶ returns the `IntSet` itself if all its elements are positive
- ▶ throws an exception otherwise

What would be the best type you can give to `assertAllPos`? Maybe:

```
def assertAllPos(s: IntSet): IntSet
```

In most situations this is fine, but can one be more precise?

$$\begin{aligned} \text{assertAllPos}(\text{Empty}) &= \text{Empty} \\ \text{---} \quad (\text{NonEmpty}(\dots)) &= \begin{cases} \text{NonEmpty}(\dots) \\ \text{throw Error} \end{cases} \end{aligned}$$

# Type Bounds

One might want to express that `assertAllPos` takes Empty sets to Empty sets and NonEmpty sets to NonEmpty sets.

A way to express this is:

```
def assertAllPos[S <: IntSet](r: S): S = ...
```

Here, “<: IntSet” is an *upper bound* of the type parameter S:

It means that S can be instantiated only to types that conform to IntSet.

Generally, the notation

- ▶  $S <: T$  means: *S is a subtype of T*, and
- ▶  $S >: T$  means: *S is a supertype of T*, or *T is a subtype of S*.

T  
↑  
S

## Lower Bounds

You can also use a lower bound for a type variable.

### Example

```
[S >: NonEmpty]
```

introduces a type parameter *S* that can range only over *supertypes* of `NonEmpty`.

So *S* could be one of `NonEmpty`, `IntSet`, `AnyRef`, or `Any`.

We will see later on in this session where lower bounds are useful.

## Mixed Bounds

Finally, it is also possible to mix a lower bound with an upper bound.

For instance,

```
[S >: NonEmpty <: IntSet]
```

would restrict S any type on the interval between NonEmpty and IntSet.



## Covariance

There's another interaction between subtyping and type parameters we need to consider. Given:

```
NonEmpty <: IntSet
```

is

```
List[NonEmpty] <: List[IntSet] ?
```

|  
NonEmpty



## Covariance

There's another interaction between subtyping and type parameters we need to consider. Given:

```
NonEmpty <: IntSet
```

is

```
List[NonEmpty] <: List[IntSet]    ?
```

Intuitively, this makes sense: A list of non-empty sets is a special case of a list of arbitrary sets.

We call types for which this relationship holds *covariant* because their subtyping relationship varies with the type parameter.

Does covariance make sense for all types, not just for List?

# Arrays

For perspective, let's look at arrays in Java (and C#).

Reminder:

- ▶ An array of T elements is written T[] in Java.
- ▶ In Scala we use parameterized type syntax Array[T] to refer to the same type.

Arrays in Java are covariant, so one would have:

```
NonEmpty[] <: IntSet[]
```

# Array Typing Problem

But covariant array typing causes problems.

To see why, consider the Java code below.

```
NonEmpty[] a = new NonEmpty[]{new NonEmpty(1, Empty, Empty)}  
IntSet[] b = a  
b[0] = Empty  
NonEmpty s = a[0]
```

*Always Store Exception*

It looks like we assigned in the last line an Empty set to a variable of type NonEmpty!

What went wrong?

*sort (Object[] a)*



# The Liskov Substitution Principle

The following principle, stated by Barbara Liskov, tells us when a type can be a subtype of another.

*If  $A <: B$ , then everything one can do with a value of type B one should also be able to do with a value of type A.*

[The actual definition Liskov used is a bit more formal. It says:

*Let  $q(x)$  be a property provable about objects  $x$  of type B. Then  $q(y)$  should be provable for objects  $y$  of type A where  $A <: B$ .*

]



## Exercise

The problematic array example would be written as follows in Scala:

```
val a: Array[NonEmpty] = Array(new NonEmpty(1, Empty, Empty))
val b: Array[IntSet] = a
b(0) = Empty
val s: NonEmpty = a(0)
```

When you try out this example, what do you observe?

- 0 A type error in line 1
- 0 A type error in line 2
- 0 A type error in line 3
- 0 A type error in line 4
- 0 A program that compiles and throws an exception at run-time
- 0 A program that compiles and runs without exception

## Exercise

The problematic array example would be written as follows in Scala:

```
val a: Array[NonEmpty] = Array(new NonEmpty(1, Empty, Empty))
val b: Array[IntSet] = a ←
b(0) = Empty
val s: NonEmpty = a(0)
```

Array (IntSet)  
↑  
Array (NonEmpty)

When you try out this example, what do you observe?

- 0 A type error in line 1
- A type error in line 2
- 0 A type error in line 3
- 0 A type error in line 4
- 0 A program that compiles and throws an exception at run-time
- 0 A program that compiles and runs without exception