

## Translation of For

## For-Expressions and Higher-Order Functions

The syntax of `for` is closely related to the higher-order functions `map`, `flatMap` and `filter`.

First of all, these functions can all be defined in terms of `for`:

```
def mapFun[T, U](xs: List[T], f: T => U): List[U] =  
  for (x <- xs) yield f(x)
```

```
def flatMap[T, U](xs: List[T], f: T => Iterable[U]): List[U] =  
  for (x <- xs; y <- f(x)) yield y
```

```
def filter[T](xs: List[T], p: T => Boolean): List[T] =  
  for (x <- xs if p(x)) yield x
```

## Translation of For (1)

In reality, the Scala compiler expresses for-expressions in terms of `map`, `flatMap` and a lazy variant of `filter`.

Here is the translation scheme used by the compiler (we limit ourselves here to simple variables in generators)

1. A simple for-expression

```
for (x <- e1) yield e2
```

is translated to

```
e1.map(x => e2)
```

## Translation of For (2)

### 2. A for-expression

```
for (x <- e1 if f; s) yield e2
```

where  $f$  is a filter and  $s$  is a (potentially empty) sequence of generators and filters, is translated to

```
for (x <- e1.withFilter(x => f); s) yield e2
```

(and the translation continues with the new expression)

You can think of `withFilter` as a variant of `filter` that does not produce an intermediate list, but instead filters the following `map` or `flatMap` function application.

## Translation of For (3)

3. A for-expression

```
for (x <- e1; y <- e2; s) yield e3
```

where  $s$  is a (potentially empty) sequence of generators and filters,  
is translated into

```
e1.flatMap(x => for (y <- e2; s) yield e3)
```

(and the translation continues with the new expression)

## Example

Take the for-expression that computed pairs whose sum is prime:

```
for {  
  i <- 1 until n  
  j <- 1 until i  
  if isPrime(i + j)  
} yield (i, j)
```

Applying the translation scheme to this expression gives:

```
(1 until n) flatMap(i =>  
  (1 until i).withFilter(j => isPrime(i+j))  
  .map(j => (i, j)))
```

This is almost exactly the expression which we came up with first!

## Exercise

Translate

```
for (b <- books; a <- b.authors if a startsWith "Bird")  
yield b.title
```

into higher-order functions.

## Exercise

Translate

```
for (b <- books; a <- b.authors if a startsWith "Bird")  
yield b.title
```

into higher-order functions.

*books flatMap (b =>  
b.authors withFilter (a => a startsWith "Bird") map (y => y.title))*

## Generalization of `for`

Interestingly, the translation of `for` is not limited to lists or sequences, or even collections;

It is based solely on the presence of the methods `map`, `flatMap` and `withFilter`.

This lets you use the `for` syntax for your own types as well – you must only define `map`, `flatMap` and `withFilter` for these types.

There are many types for which this is useful: arrays, iterators, databases, XML data, optional values, parsers, etc.

## For and Databases

For example, books might not be a list, but a database stored on some server.

As long as the client interface to the database defines the methods `map`, `flatMap` and `withFilter`, we can use the `for` syntax for querying the database.

This is the basis of the Scala data base connection frameworks `ScalaQuery` and `Slick`.

Similar ideas underly Microsoft's `LINQ`.